

Solo2 T245 / T345

Compact stand-alone label printer

A compact desktop label printer for direct thermal and thermal transfer printing. The T245 prints at 203 dpi and the T345 at 300 dpi.

Key features

- Direct thermal and thermal transfer printing
- 3.5" color display
- Takes 5" OD label rolls on a 1" core; an external holder for a full roll on a 3" core is available
- Ribbons up to 984 ft
- Real-time clock included
- Ships with a LabelDirect software license and printer driver (Windows only)



Specifications

Model	T245	T345
Resolution	203 dpi	300 dpi
Print method	Direct thermal and thermal transfer	
Max. print width	4.25"	4.17"
Max. ribbon width	4.3"	
Label roll	5" OD on a 1" core. External holder for a full roll on a 3" core available.	
Ribbon	Up to 984 ft, 1" core, ink side in or out	
Display	3.5" color display	
Real-time clock	Included	
Operating temperature	41°F to 104°F	
Humidity	25% to 85%, non-condensing	
Dimensions	8.66" W x 7.87" H x 13.07" D	
Weight	8.16 lb	
Interfaces	USB 2.0; RS-232; internal Ethernet, 10/100 Mbps; USB host (dealer option); Centronics (factory option); 802.11 a/b/g/n/ac Wi-Fi with Bluetooth 4.2 combo module; MFi Bluetooth 5.0 (factory option)	
Memory	128 MB Flash memory; 128 MB SDRAM; microSD card reader for Flash memory expansion, up to 32 GB	

Model	T245	T345
1D bar codes	Code 39, Code 93, Code128UCC, Code128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN 8, EAN 13, EAN 128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China Post, ITF14, EAN14, Code 11, TELEPEN, TELEPENN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS	
2D bar codes	TLC39, CODABLOCK F mode, PDF-417, Maxicode, DataMatrix, QR code, Aztec, Micro PDF 417, GS1 DataBar (RSS barcode)	
Software	LabelDirect software license and printer driver (Windows only)	

Works with

- LabelDirect software (license included)
- KP-200 Plus keyboard, a replacement for older Economarker systems (option)
- External label roll holder for a full roll on a 3" core (option)
- TempPac 4.33" x 984' ribbons: black wax/resin and black resin
- TempPac 4x3DTB1 poly direct thermal labels (4" x 3", 1" core)

Specifications are subject to change without notice.

TempPac, LLC · 5590 Lauby Road, Suite 10, North Canton, OH 44720 · 800.482.7225 · Fax 513-777-3283 · support@tempac.net · tempac.net