

Solo2 TM240 / TM340

Industrial thermal transfer label printer

A metal-bodied industrial label printer for direct thermal and thermal transfer printing, with a peeler and liner rewind built in. The TM240 prints at 203 dpi and the TM340 at 300 dpi.



Key features

- Direct thermal and thermal transfer printing
- Peeler with integrated liner rewind included
- 3.5" color touch screen
- Takes 8" OD label rolls on a 1" to 3" core and ribbons up to 1,476 ft
- Real-time clock included
- Ships with a LabelDirect software license and Solo printer driver (Windows only)

Specifications

Model	TM240	TM340
Resolution	203 dpi	300 dpi
Print method	Direct thermal and thermal transfer	
Max. print width	4.21"	4.16"
Max. ribbon width	4.3"	
Label roll	8" OD on a 1" to 3" core	
Ribbon	Up to 1,476 ft, 1" core, ink side in or out	
Display	3.5" color touch screen	
Real-time clock	Included	
Peeler	Included, with integrated liner rewind	
Operating temperature	32°F to 104°F	
Humidity	25% to 85%, non-condensing	
Dimensions	9.76" W x 10.79" H x 17.17" D	
Weight	20.06 lb	
Interfaces	RS-232; USB 2.0; internal Ethernet, 10/100 Mbps; USB host for data storage and keyboard	
Memory	128 MB Flash memory, 128 MB SDRAM	

Model	TM240	TM340
1D bar codes	Code 39, Code 93, Code128UCC, Code128 subsets A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, RSS-Stacked, GS1 DataBar, Code 11, China Post	
2D bar codes	PDF-417, Maxicode, DataMatrix, QR code, Aztec	
Software	LabelDirect software license and Solo printer driver (Windows only)	

Works with

- LabelDirect software (license included)
- KP-200 Plus keyboard display unit, for older Economarker systems (option)
- TemPac 4.33" × 984' ribbons: black wax/resin and black resin
- TemPac 4x3DTB3 poly direct thermal labels (4" × 3", 3" core)

Specifications are subject to change without notice.

TemPac, LLC · 5590 Lauby Road, Suite 10, North Canton, OH 44720 · 800.482.7225 · Fax 513-777-3283 · support@tempac.net · tempac.net