

Yamato PPC-200W-II

IP65 portion control scale

The standard scale for both Economarker and ScaleManager systems. A compact bench scale with a stainless-steel platform, in 20 lb and 40 lb capacities.



Key features

- Standard scale on Economarker and ScaleManager systems
- IP65, washdown capable on battery power only
- 9.1" x 9.1" stainless-steel platform
- Runs on 6 D batteries (about 3,000 hours continuous with alkaline) or an optional 110 V adapter
- RS-232 connection to the printer or PC

Specifications

Model	20 lb	40 lb
Capacity	20 lb x 0.01 lb	40 lb x 0.02 lb
Minimum weight	0.04 lb	0.08 lb
Platform	9.1" x 9.1"	
Overall size	9.8" x 9.8"	
Weight	8.6 lb	
Operating temperature	14°F to 104°F	
Humidity	30% to 85%	
Water resistance	IP65, washdown capable on battery power only	
Power	6 D batteries or optional 110 V adapter. Battery life about 3,000 hours continuous with alkaline.	
Interface	RS-232	

Works with

- Economarker systems (standard scale)
- ScaleManager systems (standard scale)
- Solo2 printers and ScaleManager PCs over RS-232

Specifications are subject to change without notice.

TempPac, LLC · 5590 Lauby Road, Suite 10, North Canton, OH 44720 · 800.482.7225 · Fax 513-777-3283 · support@tempac.net · tempac.net